

EXPLORE E+ 4 STA



SPECS

| FRAME | |
|---------------------------|--|
| SIZES | S, M, L |
| COLORS | Satin Black / Blue |
| FRAME | ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount |
| FORK | RST Volant T coil, 60mm travel, tapered steerer |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Connect XC Riser 31.8x690mm |
| STEM | Giant Contact |
| SEATPOST | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium |
| SADDLE | Selle Royal Vivo GTS/WMN |
| PEDALS | Aluminum Platform |
| DRIVETRAIN | |
| SHIFTERS | Shimano SL-M2000 |
| FRONT DERAILLEUR | - |
| REAR DERAILLEUR | Shimano Deore |
| BRAKES | Tektro HD-M275, hydraulic disc, 160/180mm |
| BRAKE LEVERS | Tektro HD-M275 |
| CASSETTE | Shimano CS-HG200, 11-36T, 9-Speed |
| CHAIN | KMC e.9 Sport, e-bike optimized |
| CRANKSET | Forged Alloy minimal Q-factor, 42T |
| WHEELS | |
| BOTTOM BRACKET | N/A |
| RIMS | Giant eX2, Tubeless Ready, 700c aluminium |
| HUBS | Giant eTracker, [F] 100x9mm QR [R] 135mm QR |
| SPOKES | Stainless steel |
| TIRES | Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready W/O Reflex |
| EXTRAS | Giant EnergyPak 3A charger |
| HYBRID CYCLING TECHNOLOGY | |
| MOTOR | Giant SyncDrive Sport |
| SENSORS | Giant PedalPlus 6-sensor technology |
| DISPLAY | Giant RideControl ONE |
| BATTERY | Giant EnergyPak 400, 36V 11.3Ah Rechargeable Lithium-Ion |
| ACCESSORIES | |
| LIGHTING | - |
| LOCK | - |
| CARRIER | - |

FEATURES

- Frame: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Fork: RST Volant T coil, 60mm travel, tapered steerer
- Shifters: Shimano SL-M2000
- Crankset: Forged Alloy minimal Q-factor, 42T
- Colors: Satin Black / Blue

Recommended Retail Price: \$2,500

GEOMETRY

| FRAME | S | M | L |
|----------------------------|-------|-------|-------|
| Seat Tube Length (inch) | 17.1 | 19.1 | 21.1 |
| Seat Tube Angle | 73.0° | 73.0° | 73.0° |
| Top Tube Length (inch) | 22.4 | 23.2 | 24 |
| Head Tube Length (inch) | 5.1 | 5.5 | 6.1 |
| Head Tube Angle | 69.5° | 69.5° | 69.5° |
| Fork Rake (inch) | 1.7 | 1.7 | 1.7 |
| Trail (inch) | 3.6 | 3.6 | 3.6 |
| Wheelbase (inch) | 43.8 | 44.1 | 45 |
| Chain Stay Length (inch) | 17.9 | 17.9 | 17.9 |
| Bottom Bracket Drop (inch) | 2.4 | 2.4 | 2.4 |
| Stack (inch) | 24 | 24.3 | 24.9 |
| Reach (inch) | 15.1 | 15.8 | 16.4 |
| Stand Over Height (inch) | 26.9 | 26.6 | 26.2 |
| Handlebar Width (inch) | 27.2 | 27.2 | 27.2 |
| Stem Length (inch) | 2.4 | 2.8 | 3.1 |
| Crank Length (inch) | 6.7 | 6.7 | 6.7 |
| Wheel Size | 700c | 700c | 700c |

All specifications and prices listed are subject to change without notice.